

<h1>Required Equipment Table</h1>		MOTORBOATS (including electric motors and jet skis)					SAILBOATS (if any type of motor attached, see motorboats)				MANUALLY PROPELLED (no motor or sail)	WHITewater (canoe, kayak, raft)
		Personal Watercraft	Less than 16' in length (Class A)	16' but less than 26' (Class 1)	26' but less than 40' (Class 2)	40' but less than 65' (Class 3)	Less than 16' in length (Class A)	16' but less than 26' (Class 1)	26' but less than 40' (Class 2)	40' but less than 65' (Class 3)	Canoes, Punts, Rowboats, Sailboards, and Rubber Rafts on Lakes	Canoes, Kayaks, and Rafts on Rivers
<b>CERTIFICATE OF NUMBER/REGISTRATION</b> (card)		X	X	X	X	X	X*1	X	X	X		
<b>REGISTRATION NUMBERS</b> (properly displayed on both sides of bow)		X	X	X	X	X	X*1	X	X	X		
<b>FLOTATION DEVICES</b>	One Type I, II, III, or Type V (wearable device) for each person on board. USCG-approved, in good condition	X*2	X*3	X*3	X	X	X*1,3	X*3	X	X	X*2, 3	X*2, 3
	One additional Type IV (throwable device) on board and readily available		X	X	X	X	X	X	X	X	X	X
<b>FIRE EXTINGUISHERS</b>	One Type B-I	X	X*4	X*4			X*4	X*4				
	Two Type B-I or one size B-II				X				X			
	Three Type B-I or one B-II plus one B-I					X				X		
<b>ROPE</b>	Stout rope—must be at least the length of the vessel	X	X	X	X	X	X	X	X	X	X	X
<b>PADDLE/OAR</b>		X	X	X	X	X	X	X	X	X	X	X
<b>BAILING BUCKET or HAND OPERATED BILGE PUMP</b>	Bailing bucket—must be at least one gallon capacity	X	X	X	X	X	X	X	X	X	X	X
<b>SOUND PRODUCING DEVICES</b>	Whistle or some other sound producing device (2 sec. plus ½ mile)	X	X	X			X	X			X	X
	Whistle or horn, hand or power operated and a bell (2 sec. plus 1 mile)				X	X			X	X		
<b>NAVIGATION LIGHTS</b>	Red and green side lights, white masthead light and stern light					X						
	Red and green combination lights and white all-round aft light		X	X	X							
	Red and green side lights and stern light						X*5	X*5	X	X	X*5	
<b>VENTILATION</b>		X	X*6	X*6	X*6	X*6	X*6	X*6	X*6	X*6		
<b>BACKFIRE FLAME ARRESTOR</b>		X*7	X*7	X*7	X*7	X*7	X*7	X*7	X*7	X*7		
<b>IGNITION SAFETY SWITCH LANYARD</b>		X*8										

- Does not apply to sailboards or windsurf boards.
- Approved PFDs must be properly worn by all occupants.
- Required to be worn on U.S. Corps of Engineer lakes on all boats up to 16 feet long.
- An extinguisher is not required if vessel is not constructed with any of the following: inboard engine, closed compartments where portable fuel tanks may be stored, double bottoms not completely sealed or flotation filled, closed living spaces, closed storage areas in which combustible, or flammable materials may be stored or permanently installed fuel tanks.

- If sidelights and sternlight are impractical, the vessel must have a lighted lantern showing a 360° white light visible for ½ mile.
- Applies to all vessels, except a vessel of “open construction” using any liquid of a volatile or toxic nature for any purpose.
- Applies to all vessels with inboard motors (does not apply to outboards).
- Lanyard of the ignition safety switch must be attached to the operator, operator’s clothing, or operator’s PFD, if equipped.